

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 January 2002 (03.01.2002)

PCT

(10) International Publication Number
WO 02/01771 A2

(51) International Patent Classification⁷: **H04H 1/02**,
H04L 12/28

(NL). VAN GRINSVEN, Petrus, A., M. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). JANSEN VAN DOORN, Arnold, K. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number: PCT/EP01/07071

(22) International Filing Date: 20 June 2001 (20.06.2001)

(74) Agent: GROENENDAAL, Antonius, W., M.; Internationaal Octrooibureau B.V., Prof Holstlaan 6, NL-5656 AA Eindhoven (NL).

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (*national*): JP, US.

(30) Priority Data:
00202220.0 27 June 2000 (27.06.2000) EP

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

(71) Applicant (*for all designated States except US*): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).


Published:
— without international search report and to be republished upon receipt of that report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): COLAK, Sel-Brian [US/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CATV SYSTEM



(57) Abstract: The CATV system according to the invention comprises at least one primary station (2) and a plurality of secondary stations (4). The primary station (2) and the secondary stations (4) are interconnected via a CATV network (6) comprising a plurality of nodes (8, 10, 12, 14). At least part of these nodes (8, 10, 12, 14) are redirection nodes (30) comprising redirection means (32) for redirecting (routing/switching) downstream data signals. In this way, it is no longer necessary to broadcast the data signals to all the nodes (8, 10, 12, 14) and secondary stations (4) in the CATV system. Instead, the data signals can be efficiently redirected to their destination and the available downstream bandwidth of the CATV network (6) can be used more efficiently.

WO 02/01771 A2

CATV system

The invention relates to a CATV system comprising at least one primary station and a plurality of secondary stations, the primary station and the secondary stations being interconnected via a CATV network, the CATV network comprising a plurality of nodes, wherein at least part of the nodes are redirection nodes comprising redirection means
5 for redirecting data signals.

The invention also relates to a CATV network.

A CATV system according to the preamble is known from United States
10 Patent 5,841,468. Modern CATV systems can deliver a whole range of interactive services to the subscribers, such as interactive television, telephone and Internet. Each subscriber has access to the CATV system by means of a secondary station. These secondary stations are able to transmit upstream data signals via a CATV network to a primary station or head end by means of a return channel. This return channel is a frequency band which is reserved for
15 the transmission of upstream signals (return signals). Furthermore, the primary station is able to transmit downstream data signals via the CATV network to the secondary stations. These downstream data signals may comprise television and/or video-on-demand programs, Internet data and/or telephone calls. In modern CATV systems, the CATV network most often is a hybrid fiber/coax network or HFC network.

20 In the known CATV system the nodes of the CATV network comprise redirection nodes having a router/switch for redirecting upstream data signals. In this way, upstream data signals can be transmitted quickly and efficiently from a first secondary station to a second secondary station. First, such upstream data signals are transmitted by the first secondary station to a redirection node which is also coupled to the second secondary station.
25 Second, on basis of the destination addresses contained in the upstream data signals, the upstream data signals are redirected by the redirection node to the second secondary station.

The known CATV system handles the transmission of the downstream data signals in a relatively inefficient way.

It is an object of the invention to provide a CATV system, which handles the transmission of downstream data signals in a more efficient way. This object is achieved in the CATV system according to the invention, which is characterized in that the data signals are downstream data signals. The invention is based upon the recognition that the redirection means can also be used to redirect the downstream data signals. Based on the destination addresses contained in the downstream data signals the redirection means can redirect (route/switch) the downstream data signals in such a way that only those parts of the downstream data signals that are destined for a certain downstream node or secondary station are redirected towards that node or secondary station. In this way, the downstream bandwidth of the CATV network is handled more efficiently as most parts of the CATV system no longer need to handle all the downstream data signals.

An embodiment of the CATV system according to the invention is characterized in that the redirection means are also comprised in the primary station. Similar to the operation of the redirection means in the redirection nodes, the redirection means in the primary station can selectively redirect the downstream data signals so that only a part of the downstream data signals is transmitted to a certain downstream node. Again, this contributes to a more efficient handling of the downstream data traffic.

An embodiment of the CATV system according to the invention is characterized in that the redirection nodes receive the downstream data signals from at least one optical fiber. There is a trend towards using binary optical transmission, i.e. the actual ones and zeros, for transmitting the downstream data signals over the fiber optical part of CATV networks. Such binary optical transmission is relatively robust to optical transmission impairments and can advantageously be used in the CATV system according to the invention: the destination addresses contained in the downstream data signals are readily available to the redirection means in the redirection nodes and no demodulation is necessary to obtain the destination addresses.

An embodiment of the CATV system according to the invention is characterized in that the CATV network has a hierarchical tree-like structure with several hierarchical levels and several branches, wherein the CATV network comprises horizontal interconnections between redirection nodes which are part of a same hierarchical level and/or diagonal interconnections between redirection nodes which are part of different hierarchical levels and of different branches. These horizontal and vertical interconnections or links can advantageously be used for load balancing of upstream and downstream data traffic. If a

default route gets congested, the links offer the possibility to redirect parts of the traffic via an alternative route (which is not overloaded) towards its destination. Moreover, the links offer redundancy in the CATV network and can even be used for self-healing purposes: if a first redirection node no longer receives data signals from a second redirection node, the redirection means of the first redirection node will no longer redirect data signals towards this second redirection node. Instead, it will redirect the data signals to another redirection node, thus providing an alternative route. Thereafter the original route can be reinstated when the first redirection node again receives data signals from the second redirection node.

An embodiment of the CATV system according to the invention is characterized in that the interconnections comprise wireless interconnections. The horizontal and diagonal interconnections or links can advantageously be formed by wireless links, e.g. wireless RF or IR links. By this measure, existing CATV systems can be upgraded relatively easy and cheap as no labor-intensive cable deployment is needed.

The above object and features of the present invention will be more apparent from the following description of the preferred embodiments with reference to the drawings, wherein:

Fig. 1 shows a block diagram of an embodiment of the CATV system according to the invention,

Fig. 2 shows a block diagram of a first embodiment of a redirection node for use in the inventive CATV system,

Fig. 3 shows a block diagram of a second embodiment of a redirection node which may be used in the CATV system according to the invention.

In the Figs., identical parts are provided with the same reference numbers.

The CATV system according to Fig. 1 is an interactive CATV system. The CATV system comprises a primary station or head end 2 and a plurality of secondary stations or network terminations 4. The primary station 2 and the secondary stations 4 are interconnected via a CATV network 6. The CATV network is a hybrid fiber/coax network or HFC network which comprises a plurality of nodes: hubs 8, fiber nodes 10 and coax amplifiers 12 and 14. In the embodiment shown in Fig. 1, the head end 2 is coupled to two hubs 8 via two fiber optical links 18, each hub 8 is coupled to two fiber nodes 10 via two

fiber optical links 18, each fiber node 10 is coupled to two coax amplifiers 12 via two coaxial links 18, and each coax amplifier 12 is coupled to a single coax amplifier 14. Furthermore, in the embodiment of Fig. 1 there are two network terminations 4 coupled to each coax amplifier 12 and 14. The CATV system according to the invention may comprise a different number of hubs 8, fiber nodes 10, coax amplifiers 12 and network terminations 4. Furthermore, the CATV network 6 may be a HFC network in which the fiber optical and coaxial parts of the network are differently proportioned with respect to each other. The CATV network 6 may even comprise a completely fiber optical network or a completely coaxial network.

The CATV network 6 has a hierarchical tree-like structure with several hierarchical levels and several branches. In Fig. 1, a first hierarchical level is constituted by the hubs 8. Similarly, the fiber nodes 10 constitute a second hierarchical level, while the amplifiers 12 and 14, respectively, constitute third and fourth hierarchical levels, respectively. Furthermore, a first branch is constituted by the (seen from the left side of the Fig.ure) first hub 8, first fiber node 10, first amplifier 12 and first amplifier 14. A second branch is constituted by the (seen from the left side of Fig.ure 1) first hub 8, first fiber node 10, second amplifier 12 and second amplifier 14. Similarly, a third branch is constituted by the (seen from the left side of the Fig.ure) first hub 8, second fiber node 10, third amplifier 12 and third amplifier 14.

Some of the nodes 8, 10, 12 and 14 which are part of the same hierarchical level are interconnected via horizontal links 20. For example, the hubs 8 are interconnected by means of such a horizontal link 20. Furthermore, some of the nodes 8, 10, 12 and 14 which are part of different hierarchical levels and of different branches are interconnected via diagonal links 22. For example, the (seen from the left of Fig. 1) second hub 8 and second fiber node 10 are interconnected by means of such a diagonal link 22. Some of the nodes 8, 10, 12, 14, but at least those nodes which are interconnected by means of a horizontal link 20 and/or a diagonal link 22, are redirection nodes 30 (see also Fig. 2). Such redirection nodes 30 comprise redirection means 32 for redirecting, e.g. routing/switching, downstream and/or upstream data signals. In this way, the data signals can selectively be distributed over the CATV-network 6 and the capacity of the CATV network 6 is handled more efficiently.

The head end 2 may also comprise the redirection means 32 for selectively redirecting the downstream data signals so that only a part of the downstream data signals is transmitted to a certain downstream node 8, 10, 12 or 14. Again, this contributes to a more efficient handling of the (downstream) data traffic.

The horizontal links 20 and/or the diagonal links 22 may comprise wireless interconnections between a transmitter and a receiver, for example wireless RF or IR interconnections. The wireless RF links may, for example, be provided at varying frequencies, mixing LMDS, MMDS or other RF regions as necessary. The wireless IR links may, for example, be provided at wavelengths of 1550nm or around 800-900nm.

Fig. 2 shows a block diagram of a first embodiment of a redirection node 30 for use in the inventive CATV system. The redirection node 30 comprises redirection means 32 for redirecting the data signals. The data signals may, at least in a part of the CATV network 6, be transmitted on basis of the Internet protocol (IP). In that case, the redirection means 32 may be formed by an IP switch. Alternatively, the data signals may be transmitted on basis of the Asynchronous Transfer Mode protocol (ATM) and the redirection means 32 may be formed by an ATM switch. The implementation of (intelligent) IP and ATM switches is well known in the art. The links 18, 20 and 22 may support the transmission of downstream and upstream data signals. Downstream data signals entering the redirection node 30 via the upper link 18 may, on basis of the destination address(es) contained in the downstream data signals and on basis of the state of the network (e.g. the state of the network may indicate that there is a need for load balancing or that a certain link is congested) be redirected by the redirection means 32 either to one of the lower links 18, to the horizontal link 20 or to the diagonal link 22. Similarly, upstream data signal which enter the redirection node 30 via one of the lower links 18 may be redirected by the redirection means 32 either to the other lower link 18, to the upper link 18, to the horizontal link 20 or to the diagonal link 22. Data signals which enter the redirection node 30 via the horizontal link 20 may be redirected by the redirection means 32 either to the upper link 18, or to one of the lower links 18, or to the diagonal link 22. Data signals which enter the redirection node 30 via the diagonal link 20 may be redirected by the redirection means 32 either to the upper link 18, or to one of the lower links 18, or to the horizontal link 20. Although not shown in Figs. 2 and 3, the redirection node 30 may be coupled to one or more further horizontal links 20 and/or one or more further diagonal links 22.

Advantageously, the data signals are transmitted in unmodulated form, i.e. baseband transmission of the actual zeros and ones, in which case the destination addresses are readily available to the redirection means 32. If the data signals are transmitted in modulated form, i.e. modulated on a RF carrier, demodulators (not shown) are needed to obtain the destination addresses from the data signals. Moreover, also modulators (not shown) may be needed to modulate the redirected data signals. In the fiber optical part of the

CATV network 6 binary optical transmission may be used for transmission of the data signals. Such binary optical transmission is relatively robust to optical transmission impairments and is an example of the above mentioned baseband transmission.

Fig. 3 shows a block diagram of a second embodiment of a redirection node 30 which may be used in the CATV system according to the invention. This second embodiment of the redirection node 30 comprises an interface unit 40 to interface with a (coaxial) part of the CATV-network in which modulated data signals are transmitted. This interface unit 40 could, for example, be based upon a Cable Modem Termination System or CMTS as known from the DOCSIS standards. Alternatively, the interface unit 40 may be based upon a Interactive Network Adapter or INA as disclosed in the DVB-RC standard. The interface unit 40 interfaces between a baseband part of the CATV network 6, i.e. the part of the CATV network 6 in which unmodulated baseband signals are transmitted over the interconnections 18, 20 and 22, and the RF part of the CATV network 6, i.e. the part of the CATV network 6 in which RF modulated signals are transmitted over the interconnections 18. These latter interconnections 18 may be logical channels, which may be based on a single physical link, and which logical channels are part of a point to multipoint connection between the interface unit 40 and a number of network terminations 4. One of the tasks of the interface unit 40 is to take care of routing the local data traffic (i.e. upstream RF modulated data signals that have a destination address on the downstream link of the same interface unit 40) and forward all other traffic to the next node in the CATV network 6.

The scope of the invention is not limited to the embodiments explicitly disclosed. The invention is embodied in each new characteristic and each combination of characteristics. Any reference signs do not limit the scope of the claims. The word "comprising" does not exclude the presence of other elements or steps than those listed in a claim. Use of the word "a" or "an" preceding an element does not exclude the presence of a plurality of such elements.


CLAIMS:

1. A CATV system comprising at least one primary station (2) and a plurality of secondary stations (4), the primary station (2) and the secondary stations (4) being interconnected via a CATV network (6), the CATV network (6) comprising a plurality of nodes (8, 10, 12, 14) wherein at least part of the nodes (8, 10, 12, 14) are redirection nodes (30) comprising redirection means (32) for redirecting data signals, characterized in that the data signals are downstream data signals.
2. A CATV system according to Claim 1, characterized in that the redirection means (32) are also comprised in the primary station (2).
3. A CATV system according to Claim 1 or 2, characterized in that the CATV network (6) comprises a HFC network.
4. A CATV system according to any one of the preceding Claims, characterized in that the redirection nodes (30) receive the downstream data signals from at least one optical fiber.
5. A CATV system according to any one of the preceding Claims, characterized in that the CATV network (6) has a hierarchical tree-like structure with several hierarchical levels and several branches, wherein the CATV network comprises horizontal interconnections (20) between redirection nodes (30) which are part of a same hierarchical level and/or diagonal interconnections (22) between redirection nodes (30) which are part of different hierarchical levels and of different branches.
6. A CATV system according to Claim 5, characterized in that the interconnections (20, 22) comprise wireless interconnections.
7. A CATV system according to Claim 6, characterized in that the wireless interconnections comprise wireless RF interconnections.

8. A CATV system according to Claim 6, characterized in that the wireless interconnections comprise wireless IR interconnections.

5 9. A CATV network (6) comprising a plurality of nodes (8, 10, 12, 14), wherein at least part of the nodes (8, 10, 12, 14) are redirection nodes (30) comprising redirection means (32) for redirecting data signals, characterized in that the data signals are downstream data signals.

1/2



2/2




FIG. 2




FIG. 3

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 January 2002 (03.01.2002)

PCT

(10) International Publication Number
WO 02/001771 A3

(51) International Patent Classification⁷: **H04H 1/02**,
H04L 12/18

Holstlaan 6, NL-5656 AA Eindhoven (NL). JANSEN
VAN DOORN, Arnold, K. [NL/NL]; Prof. Holstlaan 6,
NL-5656 AA Eindhoven (NL).

(21) International Application Number: PCT/EP01/07071

(74) Agent: GROENENDAAL, Antonius, W., M.; Interna-
tionaal Octrooibureau B.V., Prof Holstlaan 6, NL-5656 AA
Eindhoven (NL).

(22) International Filing Date: 20 June 2001 (20.06.2001)

(25) Filing Language: English

(81) Designated States (national): JP, US.

(26) Publication Language: English

(84) Designated States (regional): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE, TR).

(30) Priority Data: 00202220.0 27 June 2000 (27.06.2000) EP

Published:
— with international search report

(71) Applicant (for all designated States except US): KONIN-
KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).


(88) Date of publication of the international search report:
5 December 2002

(72) Inventors: and

(75) Inventors/Applicants (for US only): COLAK, Sel-Brian
[US/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven
(NL). VAN GRINSVEN, Petrus, A., M. [NL/NL]; Prof.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: CATV NETWORK CAPABLE OF TRANSMITTING DATA SIGNALS



(57) Abstract: The CATV system according to the invention comprises at least one primary station (2) and a plurality of secondary stations (4). The primary station (2) and the secondary stations (4) are interconnected via a CATV network (6) comprising a plurality of nodes (8, 10, 12, 14). At least part of these nodes (8, 10, 12, 14) are redirection nodes (30) comprising redirection means (32) for redirecting (routing/switching) downstream data signals. In this way, it is no longer necessary to broadcast the data signals to all the nodes (8, 10, 12, 14) and secondary stations (4) in the CATV system. Instead, the data signals can be efficiently redirected to their destination and the available downstream bandwidth of the CATV network (6) can be used more efficiently.

WO 02/001771 A3

PATENT COOPERATION TREATY

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

10069537

Applicant's or agent's file reference PHNL000377WO	FOR FURTHER ACTION		see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.
International application No. PCT/EP 01/07071	International filing date (day/month/year) 20/06/2001	(Earliest) Priority Date (day/month/year) 27/06/2000	
Applicant KONINKLIJKE PHILIPS ELECTRONICS N.V.			

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 2 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

1. Basis of the report

- a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.
- ☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).
- b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :
- ☐ contained in the international application in written form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ **Certain claims were found unsearchable** (See Box I).

3. ☐ **Unity of invention is lacking** (see Box II).

4. With regard to the **title**,

- ☐ the text is approved as submitted by the applicant.
- ☒ the text has been established by this Authority to read as follows:

CATV NETWORK CAPABLE OF TRANSMITTING DATA SIGNALS


5. With regard to the **abstract**,

- ☒ the text is approved as submitted by the applicant.
- ☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No.

- ☒ as suggested by the applicant.
- ☐ because the applicant failed to suggest a figure.
- ☐ because this figure better characterizes the invention.

1
☐ None of the figures.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 01/07071

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04H1/02 H04L12/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04H H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 592 626 A (RANGAN P VENKAT ET AL) 7 January 1997 (1997-01-07)	1,3-7,9
Y	column 4, line 52 -column 5, line 52 column 7, line 28,29; figure 1 ---	2
Y	US 5 841 468 A (WRIGHT TERRY) 24 November 1998 (1998-11-24) cited in the application column 8, line 1-15; figure 2B ---	2
X	US 4 894 825 A (KOBAYASHI HIROSHI ET AL) 16 January 1990 (1990-01-16) column 2, line 62 -column 4, line 26 column 5, line 62-68; figures 1,3,4,8 -----	1,5,9



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

30 August 2002

Date of mailing of the international search report

05/09/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Pantelakis, P

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 01/07071

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5592626	A	07-01-1997	US 5583994 A WO 9521415 A1	10-12-1996 10-08-1995
US 5841468	A	24-11-1998	AT 219873 T AU 2926597 A DE 69713584 D1 DE 895679 T1 EP 0895679 A1 WO 9741655 A1	15-07-2002 19-11-1997 01-08-2002 19-04-2001 10-02-1999 06-11-1997
US 4894825	A	16-01-1990	JP 2114055 C JP 8021926 B JP 63172538 A CA 1283195 A1	06-12-1996 04-03-1996 16-07-1988 16-04-1991